

IRIX

High Performance
POS Touch System




merlin

IRIX

High Performance POS Touch System



IRIX PTS 600

CPU

- ULV Celeron-M based 600 MHz
- Industrial PC technology
- 256MB RAM (extensible 1 GB)
- Chipset: Intel 852GME + ICH4
- Ethernet: Intel 82562 (10/100Mb)

Disk

- 2,5 Inch 60GB HDD or 4GB Flash

Display & Touch

- 15 Inch TFT, 1024x768
- 18 bit colour
- high luminous intensity TFT
- most durable, resistive Touch
- USB touch controller

I/O's

- 6x RS 232 / 4x external
- 3x USB
- LAN 10/100 Mbps
- 6 chanal surround audio
- VGA

Supply

- input 10 - 30 VDC
- powersupply 240 VAC
- power consumption 20 W (600MHz)

Details

- operating temperature 0 - 60 °C
- humidity 0 - 60 %
- measures
355 x 280 x 40 mm (W x H x D)
H = approx. 300 mm, with stand
D = approx. 56 mm, wall mounting
- Weight: 5,5 - 6 kg

Options

- swivelling stand VESA 75
- wall mounting set VESA 75

- sophisticated Design
- housing of solid Aluminium
- fanless
- ultra compact
- industrial PC based
- waterproofed (IP 64)
- high luminous TFT display
- most durable touch display
- rich in interfaces
- swivelling stand
- wall mounting set




merlin

IDS - merlin electronic
Franz-Zell-Straße 6
D-82211 Herrsching
www.merlin-electronic.de

Tel.: ++49 (0) 81 52 / 91 84 48
Fax: ++49 (0) 81 52 / 91 84 59
e-mail: info@merlin-electronic.de